






























Quanzhou Smarts Electronic & Technology Co.,Ltd
 7th Floor Hengxin building No.9 Chifeng Rd. Licheng dist.,Quanzhou,Fujian,China
 Tel: +86-(0)595-27256889 Fax: +86-(0)595-22465526
 Skype: steven821228 E-mail: steven@smartselectronic.com.cn

Products List

PRODUCT PHOTO	ITEM No.	CERTIFICATE	COVER MATERIAL	PRODUCT SIZE(mm)	INPUT VAC	OUTPUT POWER (Watt)	OUTPUT CURRENT (Amp)	OUTPUT VOLTAGE (vDC)	NET WEIGH(g)	BOX SIZE (MM)	PACK QTY. (PCS)	Gross Weight (KG)	WIRE REQUIREMENTS	waterproof rate	Warranty
Constant Current LED power supply															
	SMT-018-0350CW	CE/ROHS	Plastic	66*33*22mm	100-265	6W	350mA	10-18V	P 39g	299*224*176	200pcs/ctn	8kg/ctn	22AWG *20CM	IP20	2 years
	SMT-012-0500CW	CE/ROHS			100-265	6W	500mA	2-12V		299*224*176	200pcs/ctn	8kg/ctn	22AWG *20CM	IP20	2 years
     	SMT-030-0300CW	CE/UL/ROHS	Plastic/AL	80*36*23mm (IP20)	100-265	9W	300MA	20-30V	P 90g /AL 115g	299*224*176	100pcs/ctn	9.2kg/ctn (plastic), 12kg/ctn (Aluminum)	connecting terminal / 18AWG *20CM (waterproof type)	IP20/IP67	2 years
	SMT-026-0350CW	CE/UL/ROHS			100-265	9W	350mA	15-26V		299*224*176				IP20/IP67	2 years
	SMT-032-0350CW	CE/UL/ROHS			100-265	11W	350mA	20-32V		299*224*176				IP20/IP67	2 years
	SMT-020-0500CW	CE/UL/ROHS		62*29*20mm (IP67)	100-265	10W	500mA	10-20V		299*224*176				IP20/IP67	2 years
	SMT-014-0700CW	CE/UL/ROHS			100-265	10W	700mA	7-14V		299*224*176				IP20/IP67	2 years
	SMT-040-0300CW	CE/UL/ROHS			100-265	12W	300mA	20-40V		299*224*176				IP20/IP67	2 years
     	SMT-060-0300CW	CE/UL/ROHS	plastic/AL	140*45*28mm (IP20) / 100*40*22mm (IP67) / or 115*29*20mm (IP67)-optional	100-265	18W	300mA	40-60V	P 90g /AL 150g	299*224*176	100pcs/ctn	5.5kg/ctn (plastic) , or 8.5kg/ctn (Aluminum)	connecting terminal / 18AWG *20CM (waterproof type)	IP20/IP67	2 years
	SMT-060-0320CW	CE/UL/ROHS	plastic/AL		100-265	19W	320mA	45-60V		299*224*176				IP20 /IP67	2 years
	SMT-050-0350CW	CE/UL/ROHS	plastic/AL		100-265	16W	350mA	30-50V		299*224*176				IP20/IP67	2 years
	SMT-050-0300CW	CE/UL/ROHS	plastic/AL		100-265	15W	300mA	25-50V		299*224*176				IP20/IP67	2 years
	SMT-025-0700CW	CE/UL/ROHS	plastic/AL		100-265	17.5W	700mA	12-25V		299*224*176				IP20/IP67	2 years
	SMT-020-0900CW	CE/UL/ROHS	plastic/AL		100-265	18W	900mA	10-20V		299*224*176				IP20/IP67	2 years
     	SMT-070-0300CW	CE/UL/ROHS	plastic/AL	140*45*28mm (IP20) / 100*40*22mm (IP67) / 160*29*21mm (IP67)	100-265	21W	300mA	50-70V	P 90g/ AL 150g	299*224*176	50pcs/ctn	5.5kg/ctn (plastic) , 8.5kg/ctn (Aluminum)	connecting terminal / 18AWG *20CM (waterproof type)	IP20 /IP67	2 years
	SMT-060-0350CW	CE/UL/ROHS	plastic/AL		100-265	21W	350mA	30-60V		299*224*176				IP20 /IP67	2 years
	SMT-040-0500CW	CE/UL/ROHS	plastic/AL		100-265	20W	500mA	25-40V		299*224*176				IP20 /IP67	2 years
	SMT-048-0500CW	CE/UL/ROHS	plastic/AL		100-265	24W	500mA	35-48V		299*224*176				IP20 /IP67	2 years
	SMT-030-0700CW	CE/UL/ROHS	plastic/AL		100-265	21W	700mA	20-30V		299*224*176				IP20 /IP67	2 years
	SMT-036-0700CW	CE/UL/ROHS	plastic/AL		100-265	25W	700mA	25-36V		299*224*176				IP20 /IP67	2 years
SMT-024-1050CW	CE/UL/ROHS	plastic/AL	100-265	25W	1050mA	10-24V	299*224*176	IP20 /IP67	2 years						
 	SMT-090-0300CW	CE/UL/ROHS	plastic/AL	140*45*28mm (IP20)	100-265	27W	300mA	75-90V		299*224*176				IP20 /IP67	2 years
	SMT-080-0350CW	CE/UL/ROHS	plastic/AL		100-265	28W	350mA	60-80V		299*224*176		9kg/ctn		IP20 /IP67	2 years

PRODUCT PHOTO	ITEM No.	CERTIFICATE	COVER MATERIAL	PRODUCT SIZE(mm)	INPUT VAC	OUTPUT POWER (Watt)	OUTPUT CURRENT (Amp)	OUTPUT VOLTAGE (vDC)	NET WEIGH(g)	BOX SIZE (MM)	PACK QTY. (PCS)	Gross Weight (KG)	WIRE REQUIREMENTS	waterproof rate	Warranty	
	SMT-040-0700CW	CE/UL/ROHS	plastic/AL	(IP20) 122*58*26mm	100~265	28W	700mA	20-40V	118g/pcs (IP20) or 217g/pcs (IP67)	299*224*176	50pcs/ctn	(plastic) , or 11.5kg/ctn (Aluminum)	connecting terminal / 18AWG *20CM (waterproof type)	IP20 /IP67	2 years	
	SMT-036-0900CW	CE/UL/ROHS	plastic/AL	(IP67)or 217*29*21mm	100-265	32W	900mA	20-36V		299*224*176				IP20 /IP67	2 years	
	SMT-066-0450CW	CE/UL/ROHS	plastic/AL	(optional) (IP67)	100-265	30W	450mA	40-66V		299*224*176				IP20/ IP67	2 years	
	SMT-023-1200CW	CE/UL/ROHS	plastic/AL	(IP67)	100-265	28W	1200mA	12-23V		299*224*176				IP20 /IP67	2 years	
	SMT-060-0500CW	CE/UL/ROHS	plastic/AL	(IP67)	100-265	30W	500mA	30-60V		299*224*176				IP20 /IP67	2 years	
	SMT-070-0500CW	CE/UL/ROHS	plastic/AL	140*45*28mm (IP20) 122*58*26mm (IP67)or 217*29*21mm (optional) (IP67)	100-265	35W	500mA	40-70V	118g/pcs (IP20) or 217g/pcs (IP67)	299*224*176	50pcs/ctn	9kg/ctn (plastic) or 11.5kg/ctn (Aluminum)	connecting terminal / 18AWG *20CM (waterproof type)	IP20 /IP67	2 years	
	SMT-050-0700CW	CE/UL/ROHS	plastic/AL		100-265	35W	700mA	30-50V		299*224*176				IP20 /IP67	2 years	
	SMT-058-0700CW	CE/UL/ROHS	plastic/AL		(IP20)	100-265	40W	700mA		45~58V				299*224*176	IP20 /IP67	2 years
	SMT-100-0350CW	CE/UL/ROHS	plastic/AL		(IP67)or	100-265	35W	350mA		80-100V				299*224*176	IP20 /IP67	2 years
	SMT-120-0350CW	CE/UL/ROHS	plastic/AL		(optional)	100-265	40W	350mA		90-120V				299*224*176	IP20 /IP67	2 years
	SMT-035-1050CW	CE/UL/ROHS	plastic/AL		(IP67)	100-265	36W	1050mA		20-35V				299*224*176	IP20/ IP67	2 years
	SMT-025-1400CW	CE/UL/ROHS	plastic/AL		(IP67)	100-265	35W	1400mA		10-25V				299*224*176	IP20/ IP67	2 years
	SMT-070-0700CW	CE/UL/ROHS	Aluminum	122*58*26mm	100-265	49W	700mA	50-70V	650g	324*258*188	20pcs/ctn	13.5kg/ctn	18AWG *20CM	IP67	2 years	
	SMT-050-0900CW	CE/UL/ROHS	Aluminum		100-265	45W	900mA	35-50V		324*258*188				IP67	2 years	
	SMT-040-1050CW	CE/UL/ROHS	Aluminum		100-265	45W	1050mA	20-40V		324*258*188				IP67	2 years	
	SMT-040-1200CW	CE/UL/ROHS	Aluminum		100-265	48W	1200mA	30-40V		324*258*188				IP67	2 years	
	SMT-024-2000CW	CE/UL/ROHS	Aluminum		100-265	48W	2000mA	12-24V		324*258*188				IP67	2 years	
	SMT-040-1400CW	CE/UL/ROHS	Aluminum	130*70*43mm	100-265	56W	1400mA	25-40V	650g	375*340*200	10pcs/ctn	8.4kg/ctn	18AWG *20CM	IP67	2 years	
	SMT-025-2400CW	CE/UL/ROHS	Aluminum		100-265	60W	2400mA	12-25V		375*340*200	10pcs/ctn	8.4kg/ctn	18AWG *20CM	IP67	2 years	
	SMT-090-0700CW	CE/UL/ROHS	Aluminum		100-265	63W	700mA	65-90V		375*340*200	10pcs/ctn	8.4kg/ctn	18AWG *20CM	IP67	2 years	
	SMT-070-0900CW	CE/UL/ROHS	Aluminum		100-265	63W	900mA	50-70V		375*340*200	10pcs/ctn	8.4kg/ctn	18AWG *20CM	IP67	2 years	
	SMT-060-1050CW	CE/UL/ROHS	Aluminum		100-265	60W	1050mA	40-60V		375*340*200	10pcs/ctn	8.4kg/ctn	18AWG *20CM	IP67	2 years	
	SMT-046-1400CW	CE/UL/ROHS	Aluminum		100-265	65W	1400mA	30-46V		375*340*200	10pcs/ctn	8.4kg/ctn	18AWG *20CM	IP67	2 years	
	SMT-036-1750CW	CE/UL/ROHS	Aluminum		100-265	63W	1750mA	20-36V		375*340*200	10pcs/ctn	8.4kg/ctn	18AWG *20CM	IP67	2 years	
	SMT-030-2000CW	CE/UL/ROHS	Aluminum		100-265	60W	2000mA	20-30V		375*340*200	10pcs/ctn	8.4kg/ctn	18AWG *20CM	IP67	2 years	
	SMT-040-1800CW	CE/UL/ROHS	Aluminum	130*70*43mm	100-265	72W	1800mA	20-40V	650g	375*340*200	10pcs/ctn	8.4kg/ctn	18AWG *20CM	IP67	2 years	
	SMT-030-2400CW	CE/UL/ROHS	Aluminum		100-265	70W	2400mA	15-30V		375*340*200	10pcs/ctn	8.4kg/ctn	18AWG *20CM	IP67	2 years	
	SMT-090-0900CW	CE/UL/ROHS	Aluminum	130*70*43mm	100-265	80W	900mA	70-90V	900g	375*340*200	10pcs/ctn	8.4kg/ctn	18AWG *20CM	IP67	2 years	
	SMT-040-2000CW	CE/UL/ROHS	Aluminum		100-265	80W	2000mA	20-40V		375*340*200	10pcs/ctn	8.4kg/ctn	18AWG *20CM	IP67	2 years	
	SMT-060-1400CW	CE/UL/ROHS	Aluminum		100-265	84W	1400mA	40-60V		375*340*200	10pcs/ctn	8.4kg/ctn	18AWG *20CM	IP67	2 years	
	SMT-057-1750CW	CE/UL/ROHS	Aluminum		100-265	100W	1750mA	40-57V		315*215*210	10pcs/ctn	12kg/ctn	18AWG *20CM	IP67	2 years	
	SMT-045-2000CW	CE/UL/ROHS	Aluminum		100-265	90W	2000mA	30-45V		315*215*210	10pcs/ctn	12kg/ctn	18AWG *20CM	IP67	2 years	

PRODUCT PHOTO	ITEM No.	CERTIFICATE	COVER MATERIAL	PRODUCT SIZE(mm)	INPUT VAC	OUTPUT POWER (Watt)	OUTPUT CURRENT (Amp)	OUTPUT VOLTAGE (vDC)	NET WEIGH(g)	BOX SIZE (MM)	PACK QTY. (PCS)	Gross Weight (KG)	WIRE REQUIREMENTS	waterproof rate	Warranty
	SMT-042-2400CW	CE/UL/ROHS	Aluminum	186*68*43mm	100-265	100W	2400mA	20-42V	1210g	315*215*210	10pcs/ctn	12kg/ctn	18AWG *20CM	IP67	2 years
	SMT-100-1050CW	CE/UL/ROHS	Aluminum		100-265	105W	1050mA	80-100V		315*215*210	10pcs/ctn	12kg/ctn	18AWG *20CM	IP67	2 years
	SMT-120-1050CW	CE/UL/ROHS	Aluminum		100-265	126W	1050mA	100-120V		315*215*210	10pcs/ctn	12kg/ctn	18AWG *20CM	IP67	2 years
	SMT-084-1200CW	CE/UL/ROHS	Aluminum		100-265	100W	1200mA	65-84V		315*215*210	10pcs/ctn	12kg/ctn	18AWG *20CM	IP67	2 years
	SMT-072-1400CW	CE/UL/ROHS	Aluminum		100-265	100W	1400mA	60-72V		315*215*210	10pcs/ctn	12kg/ctn	18AWG *20CM	IP67	2 years
	SMT-050-2000CW	CE/UL/ROHS	Aluminum		100-265	100W	2000mA	30-50V		315*215*210	10pcs/ctn	12kg/ctn	18AWG *20CM	IP67	2 years
	SMT-036-2800CW	CE/UL/ROHS	Aluminum		100-265	100W	2800mA	25-36V		315*215*210	10pcs/ctn	12kg/ctn	18AWG *20CM	IP67	2 years
	SMT-110-1200CW	CE/UL/ROHS	Aluminum	222*69*43mm	/90~135V /170-265VAC	130W	1200mA	70-110V	1100g	315*215*210	10pcs/ctn	12kg/ctn	18AWG *20CM	IP67	2 years
	SMT-050-2400CW	CE/UL/ROHS	Aluminum			120W	2400mA	20-50V		315*215*210	10pcs/ctn	12kg/ctn	18AWG *20CM	IP67	2 years
	SMT-040-3000CW	CE/UL/ROHS	Aluminum			120W	3000mA	20-40V		315*215*210	10pcs/ctn	12kg/ctn	18AWG *20CM	IP67	2 years
	SMT-038-3300CW	CE/UL/ROHS	Aluminum			120W	3300mA	22-38V		315*215*210	10pcs/ctn	12kg/ctn	18AWG *20CM	IP67	2 years
	SMT-094-1400CW	CE/UL/ROHS	Aluminum			130W	1400mA	70-94V		315*215*210	10pcs/ctn	12kg/ctn	18AWG *20CM	IP67	2 years
	SMT-065-2000CW	CE/UL/ROHS	Aluminum			130W	2000mA	30-65V		315*215*210	10pcs/ctn	12kg/ctn	18AWG *20CM	IP67	2 years
	SMT-086-1750CW	CE/UL/ROHS	Aluminum	245*70*48mm	/90~135V /170-265VAC	150W	1750mA	70-86V	1210g	315*215*210	10pcs/ctn	12kg/ctn	18AWG *20CM	IP67	2 years
	SMT-063-2400CW	CE/UL/ROHS	Aluminum			150W	2400mA	40-63V		315*215*210	10pcs/ctn	12kg/ctn	18AWG *20CM	IP67	2 years
	SMT-050-3000CW	CE/UL/ROHS	Aluminum			150W	3000mA	30-50V		315*215*210	10pcs/ctn	12kg/ctn	18AWG *20CM	IP67	2 years
	SMT-045-3300CW	CE/UL/ROHS	Aluminum			145W	3300mA	30-45V		315*215*210	10pcs/ctn	12kg/ctn	18AWG *20CM	IP67	2 years
	SMT-036-4500CW	CE/UL/ROHS	Aluminum			160W	4500mA	20-36V		315*215*210	10pcs/ctn	12kg/ctn	18AWG *20CM	IP67	2 years

Note 1: The DC output/rated power can be customized, such as constant current type, can be designed at 500mA,600mA,900mA...1500mA...etc.

Note 2: Most of component are well-known brands from worldwide (ST,ON,YAGEO,Rubycon,NCC,TOSHIBA,IR,Philips...)

Note 3: The input voltage range cover: 90~135vAC/ 170~265vAC/170~305vAC/100~265vAC